



2226 Queen Anne Ave N.  
 Seattle, WA 98109, USA  
 Ph (866) 282-3384  
 Fax (206) 282-0105  
[www.silverfernchemical.com](http://www.silverfernchemical.com)

## Typical Specification

### Aromatic 150

Property	Test Method	Unit	Typical Value
API Gravity 60°F	ASTM D287		24.8 - 27.5
Specific Gravity 60°F	D1298 or D4052		0.890 - 0.905
Appearance	ASTM D4176		Bright & Clear
Aromatics Content	ASTM D 1319	Vol %	98.0 min.
Color	ASTM D 156	Saybolt	+28 min.
Distillation range	ASTM D 86	°F	
Initial boiling point		°F	350 min.
Dry point		°F	485 max.
Flash Point	ASTM D 93	°F	142 min.
Kauri-Butanol Value	ASTM D 1133	-	90 min.
Sulfur Content	ASTM D 3120		5 max.

\* This product contains approximately 25 ppm BHT as added to the manufacturing site certified storage tank.

*This specification is presented for informational purposes only. Please check with your sales representative for current specification at time of ordering. The information listed is believed to be reliable. No warranty, expressed or implied, is made to the accuracy or completeness of this information or the material or its fitness for use. The seller is not responsible for damage resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent. Purchasers shall conduct their own tests to determine the suitability of much products for particular purposes.*